Race Status API

The **listRaceDetails** operation is provided to allow customers to establish the status of a horse or greyhound race market both prior to and after the start of the race. This information is available for UK, Ireland and South African races only and is provided for information purposes only. **We cannot provide any guarantees regarding the timeliness of the data vs live /broadcasted pictures.**

listRaceDetails

Interface	Endpoint	JSON-RPC Prefix	\<method\> Example
JSON-RPC	https://api.betfair.com/exchange/scores/json-rpc/v1	\<method\>	ScoresAPING/v1.0/listRaceDetails

Operation summary

List\<RaceDetails\>	**listRaceDetails (** Set\<MeetingId\> meetingIds, Set\<RaceId\> raceIds **)**

Operations

listRaceDetails

List<RaceDetails> listRaceDetails (Set<MeetingId> meetingIds, Set<RaceId> raceIds **) throws APINGException**

Search for races to get their details.

Parameter name	Type	Required	Description
meetingIds	Set<MeetingId>		Optionally restricts the results to the specified meeting IDs. The unique Id for the meeting equivalent to the eventId for that specific race as returned by listEvents. Optionally restricts the results to the specified meeting IDs.
raceIds	Set<RaceId>		Optionally restricts the results to the specified race IDs. The unique Id for the race in the format meetingid.raceTime (hhmm). raceTime is in GMT. Optionally restricts the results to the specified race IDs. The raceID field is returned within the Race node of the Navigation Data For Applications service.

Return type	Description
List<RaceDetails>	List of retrieved race details

Throws	Description
APINGException	

Since 1.0.0

Events

This interface does not define any events.

Type definitions

RaceDetails

Race Details

Field name	Type	Required	Description
meetingId	MeetingId	✅	The unique Id for the meeting equivalent to the eventId for that specific race as returned by listEvents. Optionally restricts the results to the specified meeting IDs.
raceId	RaceId	✅	The unique Id for the race in the format meetingid.raceTime (hhmm). Optionally restricts the results to the specified race IDs.
raceStatus	RaceStatus	✅	The current status of the race.
lastUpdated	LastUpdated		This is the time the data was last updated
sequence	UpdateSequence	✅	This is the unique identifier associated to each update of the data
responseCode	ResponseCode	✅	

Type aliases

Alias	Type
UpdateSequence	long
EventId	String
EventTypeId	String
EventTime	String
UpdateType	String
LastUpdated	Date
MeetingId	String
RaceId	String

Enums

RaceStatus

Value	Description
DORMANT	There is no data available for this race.
DELAYED	The start of the race has been delayed
PARADING	The horses/greyhounds are in the parade ring
GOINGDOWN	The horses are going down to the starting post
GOINGBEHIND	The horses are going behind the stalls
APPROACHING	The greyhounds are approaching the traps
GOINGINTRAPS	The greyhounds are being put in the traps
HARERUNNING	The hare has been started
ATTHEPOST	The horses are at the post
OFF	The greyhound/horse race has started
FINISHED	The race has finished
FINALRESULT	The result has been declared (Greyhounds only)
FALSESTART	There has been a false start
PHOTOGRAPH	The result of the race is subject to a photo finish
RESULT	The result of the race has been announced
WEIGHEDIN	The jockeys have weighed in
RACEVOID	The race has been declared void
NORACE	The race has been declared a no race
MEETINGABANDONED	The meeting has been abandoned
RERUN	The race will be rerun
ABANDONED	The race has been abandoned

ResponseCode

Value	Description
OK	Data returned successfully
NO_NEW_UPDATES	No updates since the passes UpdateSequence
NO_LIVE_DATA_AVAILABLE	Event scores are no longer available or are not on the schedule
SERVICE_UNAVAILABLE	Data feed for the event type (tennis/football etc) is currently unavailable
UNEXPECTED_ERROR	An unexpected error occurred retrieving score data
LIVE_DATA_TEMPORARILY_UNAVAILABLE	Live Data feed for this event/match is temporarily unavailable, data could potentially be stale

Exceptions

APINGException

This exception is thrown when an operation fails

Error code	Description
UNEXPECTED_ERROR	The operation failed with an unexpected error
INVALID_INPUT_DATA	Invalid input data
INVALID_SESSION_INFORMATION	The session token passed is invalid or expired
INVALID_APP_KEY	The application key passed is invalid
SERVICE_BUSY	The service is currently too busy to service this request
TIMEOUT_ERROR	Internal call to downstream service timed out
NO_SESSION	A session token is required for this operation
NO_APP_KEY	An application key is required for this operation
TOO_MANY_REQUESTS	Too many requests
SERVICE_UNAVAILABLE	Service is currently unavailable

Other parameters	Type	Required	Description
errorDetails	String		The stack trace of the error
requestUUID	String		